

Turnitin Originality Report

Processed on: 22-May-2020 04:33 WIB
 ID: 1329366183
 Word Count: 2560
 Submitted: 1

Similarity Index

4%

Similarity by Source

Internet Sources:	3%
Publications:	1%
Student Papers:	4%

The Application of Cyclone Ventilator Modification for Indoor Air Sanitation By Khambali Khambali

2% match (student papers from 22-Oct-2019)
[Submitted to Universitas Jember on 2019-10-22](#)

1% match (Internet from 20-Nov-2019)
<http://eprints.ums.ac.id/70771/1/Jurnal%20Scopus%20Prof%20Absori.pdf>

1% match (Internet from 12-Dec-2019)
<http://repository.unair.ac.id/91609/1/34.%20Family%20Support.pdf>

DOI Number: 10.5958/0974-1283.2019.00052.5 [The Application of Cyclone Ventilator Modification for Indoor Air Sanitation](#) Khambali¹, Setiawan¹, [Kuat](#) Prabowo² ¹Health Polytechnic of Surabaya, Indonesia; ²Health Polytechnic of Jakarta II, Indonesia ABSTRACT There was a need to conduct research on the trial use of cyclone ventilator modification using active carbon as CO adsorbent in an indoor area so that its air fulfills the indoor air sanitation condition. This research was intended to put on cyclone ventilator modification to reduce the temperature, humidity, CO gas level and PM10 dust in indoor area so it can fulfill indoor health sanitation standard. The research used One Group Pretest Posttest Design. Cyclone ventilator modification could reduce indoor mechanic temperature by 10.919% in average, air humidity in average by 28.64%. The ability to reduce CO gas level was 28.65% in average and PM10 dust for about 52.80% after 2 hours the instrument works. Cyclone ventilator modification takes 2 hours to reduce temperature, humidity, CO gas level, and PM10 dust accumulated for 4 hours inside of mechanical room. Cyclone ventilator modification worked effectively operated inside of the room with 115.6m³ volume and was able to create a quality standard circumstances. The performance of Cyclone Ventilator Modification as an air sanitation instrument can be evaluated from energy and economical aspect in general. Secondly, those aspects shows that indoor air sanitation instrument can only works (moves) using the wind breeze. Keywords: Implementation, Cyclon, Modification, Indoor, Temperature, Humidity, CO, PM100 dust. INTRODUCTION The reduction of CO gas level after going through indoor air sanitation instrument with the suction using charcoal/active carbon of coconut shell as big as 185.3 ppm with 73.9% reduction. There is also significant different reduction of carbon monoxide(1). The reduction percentage of CO gas level by using active carbon of coconut shell is 81.54%. The effectiveness evaluation of air sanitation stated to be effective because it can reduce CO gas level more than 75%(2). Life time active carbon as CO adsorbent as long as 388 hours. This instrument is very effective because it can reduce CO gas level more than 60% in 352 hours. While, the efficiency of this instrument can be showed by the effectiveness of Corresponding Author: Khambali [Health](#)

[Polytechnic of Surabaya, Indonesia Pucang Jajar Tengah Street-56, Surabaya, Indonesia Email: khambali007@poltekkesdepkes-sby.ac.id](#) this instrument in reducing CO and its relatively small cost aspect because it doesn't use electricity energy to operate it(2). Based on the above explanation, there is a need to conduct further research for the trial use of cyclone ventilator modification by using active carbon as CO adsorbent in an indoor area so that its air fulfills the indoor air sanitation condition based on the Decree of Minister of Health No. 1405/MENKES/SK/XI/2002 concerning Health Requirements for Office and Industrial Work Environment (3). MATERIALS AND [METHOD The design of this research was One Group](#) Pretest Posttest. Materials used was coconut shell active carbon by the size of 125 um (got from sieve of 120), glue glass (sealant Seal), reagent gas absorption (CO) to collect CO sample, reagent to examine CO gas, plastic interval (diameter 0.3 cm), glass bottle, and aluminium gauze. Research instruments used in this research were Cyclone Ventilator Modification, Midget Impinger, Flow Meter, Stopwatch, Handscoon, and mask. 258 [Medico-legal Update, January-June 2019, Vol.19, No. 1](#) Sample to measure CO gas level was determined cyclone ventilator modification to reduce temperature based on purposive sampling. Sample was taken by inside of mechanical room in average was 10.919% in doing measurement as much as 10 times, to detect the every 2 hours operation, its ability to reduce air humidity average CO gas level, PM10 dust, temperature and indoor in average was 28.64% in every 2 hours operation, and wind velocity before and after the treatment (installing the ability to reduce PM10 dust in average was 52.80 cyclone ventilator modification). Data analysis process % in every 2 hours operation. It concurs the previous used paired sample t-test research about the effectiveness of cyclone ventilator modification instrument to reduce CO gas and PM 10 FINDINGS AND DISCUSSION dust level(2). Air flow speed inside of the tmechanical room increases was 48.71% in every 2 hours operation. The Room Volume of Research Spot: The volume of Mechanical Research Spot was measured by calculating The use of active carbon in cyclone ventilator room volume added by roof volume. Here was the detail modification was effective to absorb CO gas as same as Nurullita & Mifbakhuddin in their research about calculation: Monoxide Carbon Gas Absorption (CO) inside the coconut shell active carbon and durian shell explains that the presentage of CO gas reduction by using coconut shell adsorbent is 62.6%, while durian shell is 70.6%(4). This concurs and strengthens the previous research(2) that life time carbon is active as adsorbent CO as long as 388 hours, while the life time (saturated point) for filtering the dust has not been achieved. This instrument is very effective because it can reduce CO gas more than 60 % for 352 hours. Whereas, the efficiency of the instrument is shown from the effectiveness reduce CO gas and dust and the low non electricity operating cost. Structure Volume: The most used adsorbent is active carbon because it has big surface. So, it absorbs bigger energy than another Room Volume + Roof Volume adsorbent. The application of adsorption energy is mostly used in industry. The example of adsorption application $=(\rho \times l \times t) + (\frac{1}{2} \times a \times t \times p)$ vapour phase is the restoration of organic solvent used $= (4 \times 6.5 \times 4) \text{ m} + (1/2 \times 4 \times 1.45 \times 4) \text{ m}$ by substance, printing ink and textile coating. While the adsorption of liquid phase used to separate organic $= 104 \text{ m}^3 + 11.6 \text{ m}^3$ components from liquid and water waste from the $= 115.6 \text{ m}^3$ substance of organic liquid(5). Figure 1: Research Spot Volume Scetch Jaya et al. stated that emission gas NO and Nox that are adsorbted was 70%. That proves the effectiveness of Air temperature, air speed, humidity, CO gas degree, active carbon used to reduce air pollutant(6). and PM10 dust measured before and after cyclone ventilator modification was installed and operated, so The Ministry of Health Decree No. 1405/MENKES/ that there was air temperature comparison inside of the SK/XI/2002 requires that the room temperature has to be room before and after cyclone ventilator modification 18oC-26oC, the humidity is

40%-60%. Maximum dust was settled and operated. Data collection was done content inside the room in average 8 hours measurement in two hour duration before the operation of cyclone is 0.15 mg/m³. Ventilation air flows is 0.15-0.25 m/s ventilator modification operated (09.00 and 11.00 WIB) and CO gas pollutant is 25 ppm/8 hours. This research has answered that the existance of cyclone ventilator and in two hours after the operation of cyclone ventilator modification in mechanical room has created and proven modification operated (13.00 and 15.00 WIB), in one that it can be used to fulfill the requirement as air controller day for 10 days. instrument inside the room, so that the mechanical room The Ability of Cyclone Ventilator Modification to fulfill the requirement/quality standards. Reduce Temperature, Humidity, CO Gas and PM The paired sample t-test in temperatue, humidity, 10 Dust Inside of Mechanical Room: The ability of CO gas level and PM 10 dust parameter, inside the room [Medico-legal Update, January-June 2019, Vol.19, No. 1](#) 259 resulted p-value of 0.000 (there was significant difference While the air flow speed inside the room increases between of parameter before and after installing and fluctuatively as shown in Figure 2. applying cyclone ventilator modification). Figure 2: The Increase of Indoor Air Flow Speed After Installing/Operating Cyclone Ventilator Modification The problem of Cyclone Ventilator Modification application is there should be preliminary test if the instrument will be installed in another place which has higher pollutant variation with the width and volume that is as same as 115.6 m³ Time needed for cyclone ventilator modiication to reduce temperature, humidity, CO gas degree and PM10 dust until optimum limit of certain room: The meaning of optimum limit is fulfill quality standard of working area based on The Ministry of Health Decree No.1405/MENKES/SK/XI/2002(3) that is 180C-260C for room temperature, 40%-60% for humidity. Maximum dust content inside of air temperature in average measurement in 8 hours is 0.15 mg/m³. Ventilation air flows is 0.15-0.25 m/s and CO gas pollution is 25 ppm/8 hours. Time needed by cyclone ventilator modification to reduce temperature, humidity, CO gas degree and PM10 dust in this research was 2 hours. This is as same as the result of parameter massurement in first length of time, that is 2 hours after being installed and applied. It has accomplished qualification standard of working environment. However, in this research the specific time, in which minute in particular, the parameter reduction will reach the standard cannot be determined. It is because the measurement is done in the 2 hours length of time. It is not a continous measurement which can get more specific data of time. Cyclone ventilator modifivation can reduce indoor mechanical temperature in average by 0.919% and reduce air humidity in average of 28.64%. While the ability to reduce CO gas level in the average of 28.65% and decrease PM10 dust in average of 52.80% after 2 hours the instruments operates. In this research, after the instruments operates for 10 days, the ability to reduce CO gas level was 4.55% in the first day and becomes 62.88% in the tenth day. While, for the PM10 dust was 24% in the first day and becomes 82.68% in the tenth day. The longer the instrument operates, its ability to reduce CO gas and PM 10 dust will increase. Whereas, the temperature parameter and humidity creates fluctuative result. The Effectiveness of cyclone ventilator modification towards the room area/volume: The use/instalation of 1 unit cyclone ventilator modification in a room with the volume of 115.6m³ becomes effective by looking at 260 [Medico-legal Update, January-June 2019, Vol.19, No. 1](#) the ability in reducing temperature, humidity, CO gas product which is suitable for tropical climate, durable and PM10 dust level until fulfill the quality standards of and flexible, doesn't need special treatment, efficient, working room in 2 hours operational of cyclone ventilator and very quick and easy in the installation process. modification, it can also maintain the condition of the working condition in further hours. It is because there is an active carbon as cyclone ventilator modification which CONCLUSION

has a life time of 1388 working hours(2). 1. Cyclone ventilator modification could reduce The implementation of 1 unit cyclone ventilator indoor mechanical temperature in average of modification in 115.6 m³ room volume can be 10.919%, air humidity in average of 28.64%, CO recommended and proven effectively to be applied in gas level in average was 28.65% and PM10 dust industry which has working area potentially producing in average of 52.80% after 2 hours of operation. CO gas and PM10 dust level. 2. Cyclone ventilator modification in 2 hours of In this research, cyclone was operated after operation could reduce temperature, humidity, CO having pollutant parameter accumulation with 2 hours gas and PM10 dust level that were accumulated in measurement in 115.6m³ room volume which has 4 hours inside the mechanical room. accomplished quality standards. If it is assumed, cyclone 3. Cyclone ventilator modification was effectively ventilator modification operational simulation done in operated in a room with the volume of 115.6 m³ the same time with operational machine in mechanical and was able to produce the condition that meets room. It can be sure that the condition of the working the quality standards. room with that width will not exceed the determined limit (further research). 4. The performance of cyclone ventilator modification as air sanitation instrument was The excess of active carbon in the cyclone ventilator proven to be able to solve hot temperature, stuffy modification is strengthen by the research of Raso et and dirty problem in the room, reducing humidity, al. They stated that we demonstrate two steps process to make the working space more comfortable, where air sanitation system based on active carbon can be regenerated by "in situ" and eliminate volatil organic anti-rust product which was suitable for tropical compound (VOC) from indoor air by using energy climate, durable and flexible, doesn't need special efficiently(7). treatment, efficient, and is very easy and fast in the instalation process. Performance of Cyclone Ventilator Modification: Performance of cyclone ventilator modification as an RECOMMENDATION indoor air sanitation in general can be evaluated by its energy and economical aspect. Those two aspects show 1. [The application of cyclone ventilator modification that indoor air sanitation](#) operates (moves) by wind can be done by considering the instrument ability, breeze and because of the different air pressure inside room volume, and pollutant level in that room and outside of the room. Naturally, higher temperature to get optimum formulation to fulfill quality air inside the room will scientifically flow/move to the standards inside the room. lower air temperature outside the room through cyclone 2. The research of the application of cyclone ventilator modification fin, so the additional energy is ventilator modification can be a reference for not needed to operate the instrument. This is efficient in the instrument operation. another researcher to develop further step, such as the application of cyclone ventilator modification The suction power of cyclone ventilator modification to other parameter in this research. depends on air speed that hits instrument fin. Cyclone ventilator modification can handle hot temperature Source of Funding: Authors problem, stuffy and dirty in the room, reducing Ethical Clearance: Yes humidity and freshen working room (normal air circulation). Cyclone ventilator modification is anti-rust [Conflict of Interest: No Medico-legal Update, January-June 2019, Vol.19, No. 1](#) 261 REFERENCES Carbon Coconut Shell and Durian Peel. The 2nd 1. Khambali, Setiawan, Al-Jauhari S. Activated University Research Coloquium; 2015. Carbon Adsorption Effectiveness in Coconut Shell 5. Atmayudha A. Adsorption in Room Carbon Lowers Carbon Monoxide Indoor Air. Journal of Monoxide (CO) Gas with Active Carbon Coconut Environment and Earth Science. 2015;5(22):61-69. Shell and Durian Peel. Undergraduate Thesis. 2. Khambali, Setiawan, Prabowo K. Decreased Jakarta: FT-UI; 2007. Levels of Carbonmonoxide through Recovery 6. Jaya FT, Wahab AW, Maming. Adsorption of Tools on Sanitation Indoor Air. Journal of Gas Emissions Co, No, and Nox Using Activated Environment and Earth Science. 2016;6(23). Carbon from Cocoa Fruit Peel Waste

(Theobroma 3. MoH-RI. Decree of Minister of Health of Republic Cacao L.)
in Four Wheeled Motor Vehicles. of Indonesia No.
1405/MENKES/SK/XI/2002 Thesis. Makassar: UNHAS; 2005. concerning
Health Requirements for Office and 7. Raso RA, Zeltner M, Stark WJ.
Indoor Industrial Work Environment. Jakarta: Ministry Air Purification
Using Activated Carbon of Health of Republic of Indonesia; 2002.
Adsorbers, Regeneration Using Catalytic 4. Nurullita U, Mifbakhuddin.
Adsorption in Combustion of Intermediately Stored VOC. Room Carbon
Monoxide (CO) Gas with Active Industrial and Engineering Chemistry
Research. 2014;53(49):19304-19312.